


Aranet4 HOME

Wireless, portable device for measuring air quality. Measures carbon dioxide (CO₂) concentration, temperature, relative humidity, and atmospheric pressure. This sensor, belonging to the HOME sensor series, is intended to be used together with the *Aranet Home* mobile application for extended data browsing capabilities.



Product numbers

| | |
|----------|----------|
| Globally | TDSPC0H3 |
|----------|----------|

Sensor performance

General notes

- 95 % of the sensors perform within the specified accuracy limits at the time of purchase, assuming they are in an equilibrium state. For evaluation of the total measurement error, long-term drift has to be taken into account.
- Measurement time constant τ is determined at 1 m/s airflow. This constant refers to the time it takes for the sensor reading to reach 63 % of a new steady-state value in response to a step change in the environment. It essentially represents the speed at which the sensor adjusts to changes in the measured quantity.

CO₂ concentration

| | |
|----------------------|---|
| Range | 0–9999 ppm |
| Resolution | 1 ppm |
| Accuracy | $\pm(30 \text{ ppm} + 3 \% \text{ of reading})$ |
| Long term drift | Not available |
| Time constant τ | 100 s |

- CO₂ sensor of the device is calibrated at standard atmospheric pressure. CO₂ readings are pressure compensated and comply with the specifications down to 750 hPa. If the device has to be used at high altitude for a prolonged period of time, manual calibration of the unit should be performed for optimal performance. It is not intended to use the device higher than 4000 m (13'000 ft) above the sea level.
- CO₂ measurement accuracy is provided for a range 0–5000 ppm, temperature 15–35 °C (59–95 °F) and relative humidity 0–80 %. Accuracy above 5000 ppm is 10 % of reading, but not guaranteed since it is extrapolated from the calibrated range.

- If a drift of the CO₂ measurements occurs, calibration feature of the device should be used. Auto calibration mode is utilizing ABC algorithm whereas manual calibration mode demands sensor to be exposed to fresh air.

Temperature

| | | |
|----------------------|--------------|--------------|
| Range | 0–50 °C | 32–122 °F |
| Resolution | 0.1 °C | 0.1 °F |
| Accuracy | ±0.3 °C | ±0.5 °F |
| Long term drift | 0.03 °C/year | 0.05 °F/year |
| Time constant τ | 10 min | |

Relative humidity

| | |
|----------------------|---------------|
| Range | 0–85 % |
| Resolution | 1 % |
| Accuracy | ±3 % |
| Long term drift | 0.5 %/year |
| Time constant τ | To be defined |

Atmospheric pressure

| | |
|----------------------|---------------------|
| Range | 600–1100 hPa |
| Resolution | 1 hPa |
| Accuracy | +3 hPa / -2 hPa |
| Long term drift | 1 hPa/year |
| Time constant τ | 0 s (instantaneous) |

- Device measures absolute pressure, i.e., readings are not compensated for an elevation above the sea level.

General specifications

| | | |
|-----------------------------------|--|-------------------|
| Ingress protection rating | IP20 | |
| Operating temperature range | 0–50 °C | 32–122 °F |
| Operating relative humidity range | 0–85 % | |
| Dimensions | 71×71×24 mm | 2.80×2.80×0.94 in |
| Weight (incl. batteries) | 104 g | 3.7 oz |
| Enclosure material | Polycarbonate | |
| Power supply | 2 pcs AA batteries | |
| Packaging includes | 2 pcs AA alkaline batteries, configuration pin | |

Bluetooth parameters

| | | |
|----------------------------|-------------------|-------|
| Line of sight range | 10 m | 33 ft |
| Transmitter power | 4 dBm or -12 dBm | |
| Data transmission interval | 1, 2, 5 or 10 min | |

Battery lifetime

| Measurement interval | Alkaline batteries | | Lithium batteries | |
|----------------------|--------------------|--------------|-------------------|--------------|
| | Bluetooth Off | Bluetooth On | Bluetooth Off | Bluetooth On |
| 1 min | 1.4 years | 1.0 years | 1.8 years | 1.2 years |
| 2 min | 2.6 years | 1.4 years | 3.4 years | 1.9 years |
| 5 min | 5.1 years | 2.1 years | 7.2 years | 2.7 years |
| 10 min | 7.8 years | 2.3 years | >10 years | 3.1 years |

- Data provided for a device with an active Bluetooth connection considers it being paired with the *Aranet Home* mobile application and engaging in regular data transfer with the mobile phone or tablet.
- Battery lifetime data has been obtained by mathematical extrapolation and is provided for descriptive purposes only and is not intended to make or imply any guarantee or warranty.
- Battery lifetime tests and calculations performed assuming device is at 20 °C (68 °F) and using *Fujitsu Premium LR6G07* (alkaline) and *Energizer Ultimate Lithium L91* (lithium) AA batteries as reference.
- The operating temperature range may vary based on the battery type used. Generally, the range for alkaline batteries is between -20–50 °C (-4–122 °F), whereas for lithium batteries, it is -40–60 °C (-40–140 °F).

Measurement data memory specifications

| Measurement interval | Historic data availability |
|----------------------|----------------------------|
| 1 min | 3.5 days |
| 2 min | 7 days |
| 5 min | 15 days |
| 10 min | 30 days |

- The device provides access to historical data through the *Aranet Home* mobile application. For users seeking high-resolution measurement data consistently, shorter measurement interval is recommended, as frequent interval changes can impact historical data resolution.
- When transitioning to a longer measurement interval (e.g., from 1 min to 10 min), the firmware computes average values from subsets to represent the longer sampling (for instance, a 10 min average derived from ten 1 min samples).
- Likewise, when shifting to a shorter interval (e.g., from 10 min to 1 min), the memory stores additional samples mirroring the longer interval's data (such as ten 1 min samples with identical values as the original 10 min sample).

- The provided information applies to a device with the latest firmware installed. We strongly advise upgrading the firmware using the *Aranet Home* mobile application as soon as an update becomes available.

Important notes

- Device is qualified to work properly within ambient clean air. Qualification for use in harsh environment is the duty of the user of the sensor. Exposure to volatile organic compounds, acids or bases, etching substances such as H₂O₂, NH₃, shall be avoided.
- Do not leave the device in direct sunlight! Exposure to intense sunlight can adversely affect the performance and longevity of the e-ink display, potentially leading to issues like reduced contrast, diminished readability, or even permanent damage to the display pixels or electronic components. Moreover, sun exposure can also adversely impact accuracy of sensor readings.

Compliance information



Conformité Européenne



Federal Communications Commission (USA)



Innovation, Science and Economic Development Canada